LUXTRAN™

DLL948 SERIES

PRODUCT FEATURES:

- » Surface ceiling mount 9"×48" (22.86 cm × 121.92 cm)
- » Stainless steel construction for corrosion resistance
- » Drop dish clear polycarbonate lens



PROJECT INFORMATION
Job Name
Fixture Type
Catalog Number
Approved by
Approved by

SPECIFICATIONS:

HOUSING: 18-gauge, one-piece seam welded type 304 stainless steel construction. Brushed finish.

REFLECTOR: 20-gauge CRS. White TGIC polyester powder coat - 5-stage pre-treatment. Salt spray test: 1,000 hours; Reflectance: 92%.

LENS: Thermal formed 0.125" (.32 cm) polycarbonate clear lens. Lens silicone sealed to doorframe and secured with continuous lens retention angles.

DOORFRAME: 18-gauge brushed stainless steel. Continuous stainless steel piano hinge.

ELECTRICAL: Electronic ballast < 10% THD standard. See Ordering Information for multiple ballasts and optional equipment. Lamps by others.

FASTENERS: Torx® Head stainless steel fasteners standard. See Options for stainless steel center-pin reject Allen Head (AH) or Phillips Head (PH) fasteners.

INSTALLATION: For housing without wiring and mounting holes, see Field Drilled Installation Holes Option (FDIH).

WARRANTY: Limited one (1) year LED warranty. **LISTINGS:** UL and CUL listed for Wet Location.



ORDERING INFORMATION (Ex: DLL9-48-1-32-IS-1-120)

Model	Length	Lamp Quantity	Lamp Type	Ballast Type	Ballast Quantity	Voltage	Options
DLL9	48						

Nominal Length 48 4' Lamp Quantity
1 One Lamp
2 Two Lamps

Lamp Type 32 F32T8 **44** F48T8H0

RS Rapid Start Electronic <10% THD SB Specified Ballast

Instant Start Electronic <10% THD (STD)

Ballast Quantity

1 One
2 Two

Ballast Type

IS

277 Volts
 347 347 Volts
 Options
 EL Standard Lumen EL Pack

EL Standard Lumen EL I PEL High Lumen EL Pack SEL Specified EL Pack

120 Volts

Voltage

120


AH Allen Head with center pins fasteners
FDIH Field Drilled Installation Holes
FS Single Fuse & Holder
PH Phillips Head fasteners
PSS Painted Stainless Steel Housing

Holes

SSIN Stainless Steel Interior

DIMENSIONAL DATA

CROSS SECTION



1/2" (1.27 cm) EMT Hole 51.00" 129.54 cm 9.312" 23.65 cm 91.44 cm Ø.312" (Ø.79 cm)

MOUNTING HOLES

