# LUXTRAN™

## LTD SERIES

### **PRODUCT FEATURES:**

- » Surface mount; ceiling or wall  $1'\times4'$  (30.48 cm  $\times$  122 cm)
- » One piece, stainless steel housing; 20 gauge seam welded
- » Cam latches for ease of maintenance



PROJECT INFORMATION
Job Name
Fixture Type
Catalog Number
Approved by

### SPECIFICATIONS:

HOUSING: 20-gauge, one piece seam welded Type 316 stainless steel construction with two (2) 12-gauge 316 stainless steel TIG welded mounting brackets on the top.

REFLECTOR: .016 specular aluminum mounted on top of a 20-gauge 316 stainless steel removable tray.

DOORFRAME: 18-gauge Type 316 stainless steel, supported to housing with aircraft cables and eight stainless steel cam latches. Sealed to housing with gasket.

LENS: .250" (.64 cm) clear tempered glass. Lens silicone caulk sealed to doorframe and secured with 16-gauge type 316 stainless steel continuous lens retention "L" brackets.

HARDWARE: Four (4) stainless steel 1/4 turn fasteners for easy removal of the electrical tray.

**ELECTRICAL:** Electronic ballast. Lamps by others. **LAMPS:** Type as specified — see Ordering Information.

INSTALLATION: Surface or wall mount.

**WARRANTY:** Limited one (1) year Kenall flourescent warranty. **LISTINGS:** UL listed for Wet Location. Certified IP66 per IEC 60598.




#### ORDERING INFORMATION (Ex: LTD14-XH-2-28-RS-120)

Model LTD14	Door/Housing	Lamp Quantity	Lamp Type	Ballast Type	Voltage	Options
	Door Housing Mt		Lamp Type	Ballast Type	Voltage	Options
	XH 20-Ga Type 316 SS		<b>28</b> F28T5	RS Rapid Start Electronic	<b>120</b> 120 Volts	<b>FS</b> Fuse & Holder
	PXH 20-Ga Type 3	16 SS; Painted	<b>54</b> F54T5H0	SB Specified Ballast (Consult factory)	<b>277</b> 277 Volts	<b>TB</b> Terminal Block

#### Lamp Quantity 2 Two

DIMENSIONAL DATA

# CROSS SECTION



### BACK / TOP VIEW

