

MEDMASTER™

Patient Room Luminaires

MAC2B SERIES – LF SURFACE MOUNT

PRODUCT FEATURES:

- » Surface ceiling mount – 1'x4', 2'x2', 2'x4'
- » Dual side baskets provides indirect ambient lighting
- » Ingress barrier door provides consistent surface for cleanability



PROJECT INFORMATION

Job Name _____

Fixture Type _____

Catalog Number _____

Approved by _____

SPECIFICATIONS

HOUSING: 18-gauge CRS. One-piece seam welded construction. White TGIC polyester powder coat – 5-stage pre-treatment. Salt spray test 1,000 hours. Reflectance 92%. See Ordering Options for Antimicrobial Finish.

DOORFRAME: Heavy duty extruded aluminum with clear satin anodized finish. Doorframe supported to housing with aircraft cables (IB-AC) to provide NSF2 listing, or an optional continuous hinged doorframe (IB-HD). Select in ordering options below. Phillips head stainless steel fasteners secure door to housing – 8 with IB-AC (1x4, 2x2), 10 with IB-AC (2x4) and 2 with IB-HD (2x2) and 3 with IB-HD (1x4, 2x4). Extruded closed cell gasket seals doorframe to housing.

LENS: .125" clear high impact acrylic. Sealed to extruded aluminum frame with a vinyl gasket.

LAMP SHIELDING: Perforated aluminum basket with pearlescent acrylic diffuser – white TGIC polyester powder coat finish.

ELECTRICAL: Fluorescent electronic ballasts, high power factor (<10% THD.) See Ordering Information for optional equipment. Lamps by others.

INSTALLATION: Four .312" diameter holes.

WARRANTY: Limited one (1) year Kenall fluorescent warranty.


LISTINGS: UL and CUL Listed for Wet Location and UL certified IP65 per IEC 60598. NSF2 Splash Zone (IB-AC only).



ORDERING INFORMATION (Ex: MAC2B22-S-2-17-IS-1-120-IB-AC)

Model	Mounting	Lamp Qty/Type	Ballast Type	Ballast Qty	Voltage	Doorframe	Options	Accessories
S		IB-						
Model		2x2	Ballast Type				Options	
MAC2B14 1'x4'		2-14† Two F14T5	IS Instant Start Electronic <10% THD (T8)				EL Standard Lumen One-Lamp EL Pack (347V dry location only)	
MAC2B22 2'x2'		4-14† Four F14T5	RS Rapid Start Electronic <10% THD (T5, T8, T5HO)				AMF Antimicrobial Finish on exposed painted surfaces	
MAC2B24 2'x4'		2-17 Two 17T8	SB Specified Ballast				DLN LED Night Light w/Light Level Control	
		4-17 Four 17T8					TN† Night Light – 5/7/9 Watt PL (Lamp supplied by other)	
Mounting			Ballast Quantity				FS Single Fuse & Holder (1 per ballast)	
S Surface		2x4	1 One				LVC† Low Voltage Controller (See Application Guide or consult factory for switching options)	
		2-28† Two F28T5	2 Two (2x2, 2x4 only)				RF† Radio Frequency Filter (1 per ballast)	
Lamp Type		4-28† Four F28T5					Accessory	
1x4		2-32 Two F32T8	Voltage				TH 1/2" Trade Size Threaded Hub	
2-28† Two F28T5		4-32 Four F32T8	120 120 Volts					
2-32 Two F32T8		2-54 Two F54T5HO	277 277 Volts					
2-54 Two F54T5HO		4-54 Four F54T5HO	347 347 Volts					
			Doorframe					
			AC Ingress Barrier w/Aircraft Cables (Std.)				tn/a with 347V	
			HD Ingress Barrier w/Continuous Piano Hinge (not NSF2 listed)					

DIMENSIONAL DATA



DIMENSIONAL DATA (IN INCHES)

	A	B	C	D
1x4	5.13	10.60	32.00	4.25
2x2	5.56	22.60	12.00	12.00
2x4	5.56	22.60	36.00	12.00



www.kenall.com | P: 800-4-Kenall | F: 262-891-9701 | 10200 55th Street Kenosha, Wisconsin 53144, USA

A brand of **legrand**

This product complies with the Buy American Act: manufactured in the United States with more than 50% of the component cost of US origin. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2019 Kenall Mfg. Co.