MILLENIUM METREX™

METER SERIES

PRODUCT FEATURES:

- » Surface mount wall or ceiling
- » Emergency Remote Unit
- » ADA compliant
- » 16-gauge cold rolled steel baseplate
- » UV-stabilized high impact clear wraparound polycarbonate lens



PROJECT INFORMATION
Job Name
Fixture Type
Catalog Number
Approved by

SPECIFICATIONS

LENS/HOUSING: One-piece wraparound lens/housing, UV-stabilized, high impact, virgin injection molded polycarbonate. Nominal thickness .120".

BASEPLATE: 16-gauge CRS. Baseplate provided with four-point mounting holes, one wireway hole – see Cross Section/Details. White TGIC polyester powder coat – 5-stage pre-treatment. Salt spray test: 1,000 hours; Reflectance: 92%.

GASKET: Die-cut closed cell neoprene gasket seals lens/housing to mounting surface.

HARDWARE: Four stainless steel Torx® T-20 with center pin fasteners secure lens/housing to baseplate.

ELECTRICAL: 12V AC or DC operation. Field adjustable emergency lamps. Powered by external 12VDC power supply as provided by Kenall METEC, METEL HC.

INSTALLATION: Standard four-point mounting required for <u>Peace of Mind Guarantee</u>®.

LISTINGS: UL and CUL listed for Wet Location. Meets or exceeds UL924 and NFPA 101 standards.













ORDERING INFORMATION (Ex: METER-MW-2-6.5L-12VAC/DC)

Model Finish Lamp Qty Voltage Options Lamp Type **METER** 6.5L 12VAC/DC

Finish

MB Matte Black MW Matte White **Lamp Quantity**

1 Internal Lamp

2 Internal Lamps

Lamp Wattage/Type

6.5L 6.5W LED

Voltage

12VAC/DC 12 Volt AC/DC

Options

PH Phillips Head Fasteners

DIMENSIONAL DATA



