

# MIGHTY MAC™

## MMEX SERIES

### PRODUCT FEATURES:

- » Surface mount – wall or ceiling
- » 14-gauge cold rolled steel or stainless steel housing
- » Indirect Red or Green LED
- » Single and Double Face
- » Ligature resistant construction



### PROJECT INFORMATION

Job Name \_\_\_\_\_

Fixture Type \_\_\_\_\_

Catalog Number \_\_\_\_\_

Approved by \_\_\_\_\_

### SPECIFICATIONS

**HOUSING:** One-piece die-formed prime 14-gauge grade material as specified – see ordering information. Corners continuously seam welded and smooth with no post grinding (TIG).

**DOOR:** One-piece die-formed prime grade 14-gauge. Corners continuously seam welded and smooth with no post grinding (TIG).

**LEGEND:** Legend illuminated by internal high output LEDs. Lettering six inches high with .750 inch stroke. Internal panels with stencil cut letters and red or green filter panel. External panel .188" thick clear polycarbonate. Universal arrows.

**FASTENERS:** Hardened security screws as specified – see ordering information.

**FINISH:** TGIC polyester powder coat – 5-stage pre-treatment. Salt spray test: 1,000 hours; Reflectance: 92%. See Options for black exterior.

**ELECTRICAL:** 624 nm Red or 527 nm Green LED light source. Electrical components mounted to removable high impact, injection molded polycarbonate chassis. Exit Ready – can power one Kenall METSS Satellite Exit.

**OPTIONS:** Sealed nickel-cadmium Emergency Battery Pack (EL) with standard deep cycle battery conditioning, self test and self diagnostic circuitry, remote laser activated test switch, protected mechanical test switch and status indicator. Provides 120 minutes of emergency operation. Emergency Battery Pack (EL) suitable for 10°C to 45°C (50°F to 113°F). Cold Weather Emergency Battery Pack (CEL) suitable for -45°C to 45°C (-49°F to 113°F). (When used with a Kenall METSS, this fixture provides 90 minutes of emergency operation.)

**LISTINGS:** UL and CUL listed for Wet Location. UL Classified IP65 per IEC 60598. Meets or exceeds UL924 and NFPA 101 Standards. Meets or exceeds CSA and NRCAN requirements. Ligature resistant construction.



### ORDERING INFORMATION (Ex: MMEX-1-0-G-DT-1)

Model	Face	Hsg. and Dr. Material	Legend Color	Voltage	Fasteners	Options	Accessories
<b>MMEX</b>							
<b>Face</b>		<b>Housing and Door Material</b>		<b>Voltage</b>		<b>Options</b>	
1	Single Face	0 14-Ga CRS (Painted)		DT 120/277 Volts		BLK Black Exterior (n/a with brushed housing and door material)	
2	Double Face	3 14-Ga SS (Painted)		DTC 120/347 Volts		EL Standard Emergency Battery Pack	
		6 14-Ga SS (Brushed)				CEL Cold Weather Emergency Battery Pack	
		<b>Legend Color</b>		<b>Fasteners</b>		XAC Auxiliary AC Supply (Matches Voltage Selection)	
		G Green		1 Torx® T-20 w/ Center Pin		XDC Auxiliary DC Supply (6-24 Volts)	
		R Red		2 Allen Head w/ Center Pin		<b>Accessories</b>	
						LP Laser Pointer	



www.kenall.com | P: 800-4-Kenall | F: 262-891-9700 | 10200 55th Street Kenosha, Wisconsin 53144, USA  
 This product can comply with the latest domestic preference legislation, such as the Buy American Act (BAA), Trade Agreement Act (TAA), Build America, Buy America Act (BABA), and others. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2024 Kenall Mfg. Co.

A brand of Legrand

# MIGHTY MAC™

## MMEX SERIES

### DIMENSIONAL DATA

