


MILLENIUM™ SQUARE

MS11 SERIES – DEEP PROFILE HOUSING

PRODUCT FEATURES:

- » Surface mount – ceiling (FD & CD only) or wall mount;
12"W×12"W×6"D (CD, ED, FD)
16"W×16"W×7"D (DD)
- » Peace of Mind Guarantee®
- » Dust and water protected to IP64 standards



FD



DD



CD



ED

SPECIFICATIONS

HOUSING: Marine grade die-cast aluminum. Integral heat sinks. Housing flange interlocks and wraps around lens base producing maximum moisture deflection and resistance to prying. Housing provided with four standoff mounting holes, one 3/4" NPT tapped hole on back of housing, four 3/4" NPT tapped and plugged holes on sides of housing – see Dimensional Data. Standard matte black, dark bronze or matte white exterior TGIC polyester powder coat – 5-step pre-treatment. See Ordering Information for optional finishes.

REFLECTOR: Full reflector/wire cover – 92% reflectivity.

LENS: UV-stabilized, high impact resistant, virgin injection molded polycarbonate. High efficiency blondel fluted lens maximizes uniformity. Lens secured with four concealed captive Torx® with center pin fasteners. Exclusive water channeling lens design provides 360° ingress protection.

LENS BASE/EYELID: High impact resistant, injection molded matte black, dark bronze or matte white polycarbonate. Optional Light Gray, Silver, Forest Green or Custom Color (see Ordering Information below) are chemically bonded, impact resistant finishes.

GASKETING: Die-cut, closed cell EPDM self adhesive gasket seals housing to mounting surface. Closed cell, silicone "O" ring gaskets positioned and friction secured in gasket channels of lens base and housing.

HARDWARE: Four stainless steel Torx® T-20 with center pin fasteners.

ELECTRICAL: Available in 3500K, 4000K, and 5000K color temperatures, 80 CRI. 120-277VAC, 50/60Hz electrical input with high power factor electronic, constant-current driver (>.90 PF). Standard 0-10V dimming with 1-100% range; maximum driver source of 200 µA. Optional embedded microwave motion sensor (MS) has factory default settings of 20 minute time out, dims down to 30%.

SENSOR & CONTROLS: Optional sensor available with compatible third party controls. To see the full list of compatible controls, [click here](#).

PHOTOMETRICS: Photometry tested to the IESNA LM-79-08 standard by an ILAC/ISO17025 accredited laboratory. For additional photometric information, go to www.kenall.com.

WARRANTY: Limited five (5) year LED warranty. [Peace of Mind Guarantee](#) against breakage.

LISTINGS: UL and CUL listed for Wet Location (listing includes Emergency Battery Pack "LEL" option). UL certified IP64 per IEC 60598. Luminaire tested to an IK10 impact protection rating per IEC 60068-2-75:1997-08.



ORDERING INFORMATION (Ex: MS11FD-PP-MW-20L40K-DV)

Model	Lens Type	Finish	Lamp Type	Voltage	Options
PP					
Model			Lamp Type		Options
MS11CD	Cross		10L35K 10 Watt 3500K LED		LEL LED Emergency Battery Backup (n/a with 347V; also n/a with 50L)
MS11DD	Diamond Eyelid		10L40K 10 Watt 4000K LED		BPC* Photo Control – Shielded Button Type (120V or 277V only)
MS11ED	Eyelid		10L50K 10 Watt 5000K LED		20KV 20KV/KA Surge Protection per IEEE/ANSI C62.41.2 Cat. A
MS11FD	Full Face		20L35K 20 Watt 3500K LED		FS Single Fuse & Holder
			20L40K 20 Watt 4000K LED		NAT Natatorium Environment Option
			20L50K 20 Watt 5000K LED		MS Motion Sensor (n/a with 347V)
Lens Type			50L35K† 50 Watt 3500K LED		
PP	Pearlescent Polycarbonate		50L40K† 50 Watt 4000K LED		
			50L50K† 50 Watt 5000K LED		
Finish			Voltage		
DB	Dark Bronze		120 120 Volts		† Available with MS11CD and MS11FD only
FG	Forest Green		277 277 Volts		* BPC n/a in conjunction with LEL or MS options
LG	Light Gray		347 347 Volts		
MB	Matte Black		DV 120-277 Volts		
MW	Matte White				
SL	Silver				
CC	Custom Color (Consult factory)				

PROJECT INFORMATION

Job Name _____

Fixture Type _____

Catalog Number _____

Approved by _____



www.kenall.com | P: 800-4-Kenall | F: 262-891-9700 | 10200 55th Street Kenosha, Wisconsin 53144, USA
 This product is able to comply with the latest domestic preference legislation, such as the Buy American Act (BAA), Trade Agreement Act (TAA), Build America, Buy America Act (BABA), and others. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2024 Kenall Mfg. Co.

A brand of **Legrand**

MILLENNIUM™ SQUARE


MS11 SERIES – DEEP PROFILE HOUSING

PERFORMANCE

Model	Lamp Type	Initial Delivered Lumens		Input Power (W)	Drive Current (mA)	Estd. L70 LED Life (hrs)
		@ 25°C (lm)	Efficacy (lm/W)			
MS11FD	10L35K	1,307	102	13	94	130,000
	10L40K	1,307	102	13	94	130,000
	10L50K	1,425	111	13	94	130,000
	20L35K	2,523	106	24	94	130,000
	20L40K	2,523	106	24	94	130,000
	20L50K	2,750	116	24	94	130,000
	50L35K	5,386	92	58	117	60,000
	50L40K	5,386	92	58	117	60,000
	50L50K	5,871	101	58	117	60,000
MS11CD	10L35K	1,050	82	13	94	130,000
	10L40K	1,050	82	13	94	130,000
	10L50K	1,144	89	13	94	130,000
	20L35K	2,026	85	24	94	130,000
	20L40K	2,026	85	24	94	130,000
	20L50K	2,208	93	24	94	130,000
	50L35K	4,740	81	58	117	60,000
	50L40K	4,740	81	58	117	60,000
	50L50K	5,166	89	58	117	60,000
MS11DD	10L35K	1,070	84	13	54	130,000
	10L40K	1,070	84	13	54	130,000
	10L50K	1,167	91	13	54	130,000
	20L35K	2,067	87	24	94	130,000
	20L40K	2,067	87	24	94	130,000
	20L50K	2,253	95	24	94	130,000
MS11ED	10L35K	1,023	80	13	94	130,000
	10L40K	1,023	80	13	94	130,000
	10L50K	1,116	87	13	94	130,000
	20L35K	1,975	83	24	94	130,000
	20L40K	1,975	83	24	94	130,000
	20L50K	2,153	91	24	94	130,000


Info subject to change. Visit www.kenall.com for IES files and additional information.

Model: MS11FD-PP-MW-50L40K-DCC-DV



Max Candela = 1746 Located At Horizontal Angle = 0, Vertical Angle = 0
 1 - Vertical Plane Through Horizontal Angles (0-180) (Through Max. Cd.)
 2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)

Model: MS11ED-PP-MW-20L40K-DCC-DV



Max Candela = 718 Located At Horizontal Angle = 0, Vertical Angle = 65
 1 - Vertical Plane Through Horizontal Angles (0-180) (Through Max. Cd.)
 2 - Horizontal Cone Through Vertical Angle (65) (Through Max. Cd.)



www.kenall.com | P: 800-4-Kenall | F: 262-891-9700 | 10200 55th Street Kenosha, Wisconsin 53144, USA
 This product is able to comply with the latest domestic preference legislation, such as the Buy American Act (BAA), Trade Agreement Act (TAA), Build America, Buy America Act (BABA), and others. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2024 Kenall Mfg. Co.

A brand of Legrand

MILLENIUM™ SQUARE

MS11 SERIES – DEEP PROFILE HOUSING

DIMENSIONAL DATA

MS11FD, CD, ED

MS11DD

