PROJECT	Job Name	Catalog	Number
NFORMATION	Fixture Type	Approve	d by

# **MEDMASTER SOFTSTEP™ STEPLIGHTS**

# Patient Room Steplight

# **MSL SERIES – FABRICATED**

#### **PRODUCT FEATURES:**

- » Recessed wall mount Rectangle available in horizontal or vertical orientation
- » NSF2 listing for cleanability
- » White, Amber, or Red LED lamp options
- » ADA Compliant
- » Ligature resistant construction



**MSLS** 





MSLR-H MSLR-V

#### **SPECIFICATIONS**

HOUSING: 18-gauge CRS. White TGIC polyester powder coat - 5-stage pre-treatment. Salt spray test: 1,000 hours; Reflectance: 92%. Four .875" knockouts.

FACEPLATE: 18-gauge CRS (powder coated) or Type 304 Stainless Steel. Faceplate secured to housing with stainless steel screws. Internal louver is positioned behind lens for easy cleaning of entire faceplate. See Faceplate Finish in Ordering Information for color selection.

LENS: Polycarbonate, acrylic or tempered glass lens. Polycarbonate and acrylic lens available in clear, prismatic or translucent white. Tempered glass available in clear or prismatic.

ELECTRICAL: 120VAC or 277VAC 60Hz input. Available in white, red, or amber LED.

INSTALLATION: Two adjustable mounting brackets for new construction.

PHOTOMETRICS: Photometry tested to the IESNA LM-79-08 standard by an ILAC/ISO17025 accredited laboratory. For additional photometric information, go to www.kenall.com.

WARRANTY: Limited five (5) year LED warranty.

LISTINGS: UL and CUL Listed for Damp Location. See Option for Wet Location listing. NSF2 Splash/Non-Food Zone. Ligature resistant construction.



#### ORDERING INFORMATION (Ex: MSLR-H-F-0-GW-CP-WLL-120-2)

Model Faceplate Faceplate Material Faceplate Finish Lens Type Lamp Type Voltage Fasteners Option Packaging

#### Model

MSLR-V Rectangle Vertical Rectangle Horizontal MSLR-H

MSLS Square

### Faceplate

Full Face Internal Louver Slotted St

### **Faceplate Material**

18-Ga CRS (Painted) 18-Ga Type 304 SS

### **Faceplate Finish**

GW Gloss White Antimicrobial MW Matte White Antimicrobial MB Matte Black Antimicrobial

BE Beige

DB Dark Bronze LG Light Gray

١٧ Ivory

CS Cool Satin Painted Anodized ws Warm Satin Painted Anodized

Brushed SS (only available with Faceplate Material Option 1)

#### Lens Type Polycarbonate

Clear Polycarbonate

Pearlescent Polycarbonate

.125" #12 Prismatic Polycarbonate 2

<u>Acrylic</u>

.125" Clear High Impact Acrylic

PIA Pearlescent Acrylic

.125" #12 Prismatic High Impact Acrylic

**Tempered Glass** 

.187" Clear Tempered Glass .188" Textured Tempered Glass TG

### **Lamp Type**

Low Lumen

WLL 4000K White Low Lumen LED (0.05A/0.55W)

**ALL** Amber LED (0.05A/0.50W) **RLL** Red LED (0.05A/0.50W)

WHL 4000K White High Lumen LED (0.10A/1.10W) (n/a w/Square)

### Voltage

**120** 120 Volts 277 Volts

#### **Fasteners**

Torx Head w/Center pin (2)

3 Phillips-head Fasteners (2)

### Option

Wet Location Listed

# **Packaging**

SP\*\* Split Packaging (min. quantity 10 pcs)

- † n/a with clear lens
- \* Internal Louver (L) available with clear lens option only
- \*\*Rough-In Box (Box 1), Fixture Section (Box 2)

# **MEDMASTER SOFTSTEP™ STEPLIGHTS**


Patient Room Steplight

## **MSL SERIES – FABRICATED**


**DIMENSIONAL DATA** 

MSLS


### FRONT VIEW




SIDE VIEW





WALL CUTOUT




MSLR-H









MSLR-V







DIMENSIONAL DATA (IN INCHES)										
	Α	В	C	D	E	F	G			
MSLS	5.00	5.00	3.25	0.30	3.12	4.63	3.38			
MSLR-H	4.38	7.00	3.25	0.30	3.12	6.63	3.38			
MSLR-V	7.00	4.38	6.50	0.30	3.12	3.38	6.63			

