

LUXTRAN™ Remote Driver for Tunnel Applications

RD700 SERIES

PRODUCT FEATURES:

- » Remotely powers Kenall LTL and LTS Series LED luminaires via constant-current DC
- » High-efficiency (>90%) drivers with dedicated heat sinks and 20kV built-in surge suppression for long-life operation
- » Simplified servicing of drivers via patent-pending tool-less, quick-release mechanism
- » Stainless steel structural construction with marine-grade aluminum heat sinks
- » Suitable for placement most convenient to servicing
- » Wall or ceiling orientations; ADA compliant for wall orientations
- » 10 Year limited product warranty



PROJECT INFORMATION

Job Name _____

Fixture Type _____

Catalog Number _____

Approved by _____

SPECIFICATIONS

CHASSIS: 16-gauge Type 304 or Type 316 stainless steel enclosure with one-piece, seam-welded construction; 2B finish; passivated post-welding. 14-gauge die-formed and welded mounting points; custom mounting detail to tunnel structure available.

HEAT SINKS: Type 413 marine-grade die-cast aluminum, coatings to withstand either 1,000 hour or 5,000 hour salt fog test per ASTM B117. Electrically insulated from stainless steel chassis.

DOORFRAME: 16-gauge Type 304 or Type 316 stainless steel doorframe with one-piece, seam-welded construction; 2B finish; passivated post-welding. Full length stainless steel hinge. Lockable rotary latches (lock by others) constructed of matching grade stainless steel.

GASKETING: One-piece extruded silicone with molded corners.

LED DRIVERS: Up to six (6) electronic LED drivers. 277-480 VAC, 50/60Hz single-phase input; <20% THD, >0.90 PF. Minimum 90% electrical efficiency. 1050mA or 1400mA Class I constant-current output—see Circuit Detail for information on drive current and load configuration requirements. Standard 0-10V dimming with 0-100% range. EMC compliant with FCC 47 CFR Part 15, Class B. Passes IEC 61000-4-4 EFT and IEC 61000-4-5 (Class 4) surge evaluation. Driver quick-release mechanism provides mechanical and electrical disconnection of individual drivers for servicing purposes.

ELECTRICAL: Screw connection terminal blocks for line-voltage inputs (up to three circuits—#2-14AWG), earth ground, low-voltage dimming inputs and DC load to luminaires. Compatible with relay/step-dimming or 0-10V-based control systems. Replaceable external surge suppressor per driver, rated to 20kA/kV per IEEE/ANSI C62.41 Cat A.

OPTIONAL CONTROLS: Optional control module available with compatible third party controls. To see the full list of compatible controls, [click here](#).

INSTALLATION: Wall or ceiling orientation, see Ordering Information for selection. Mounting hardware provided by others. Ambient temperature rating is -40°C to 40°C.

WARRANTY: Limited ten (10) year warranty.

LISTINGS: Enclosure is certified to UL Standards by Intertek Testing Laboratory for Wet Location. IP66 rating per IEC 60529. Rated to NEMA 4X. Luminaire is 3G vibration tested per ANSI C136.31.



ORDERING INFORMATION (Ex: RD700-SM-6-1050-277-304-5KF)

Model	Mounting Design Detail	Driver Qty	Output Current	Input Voltage	Housing Material	Heat Sink Finish	Options
RD700							
Mounting Design Detail		Output Current		Housing Material		Options	
SM	Standard Mounting Detail (as shown)	1050	1050mA Output	304	Type 304 Stainless Steel	LPCM	NYX Hemera Local Programmable Control Module (for Power Line Control); click here for specifications)
CM	Custom/Project-Specific Mounting (consult factory)	1400	1400mA Output	316	Type 316 Stainless Steel		
Driver Quantity		Input Voltage		Heat Sink Finish			
4	Four	277	277 Volts	1KF	1,000 Hour Finish		
6	Six	347	347 Volts	5KF	5,000 Hour Finish		
		480	480 Volts				

ELECTRICAL CHARACTERISTICS

Driver Qty	Product Compatibility	Driver Output (per Driver)		Max. Input Current (per Driver)			Max. Input Power per Driver	Max. Total Input Power
		Output Current	Output Voltage	277 VAC	347 VAC	480 VAC		
4	LTS	1050 mA	240-320 VDC	1.39 A	1.11 A	0.80 A	385 W	1540 W
6	LTS	1050 mA	240-320 VDC	1.39 A	1.11 A	0.80 A	385 W	2310 W
4	LTS/LTL	1400 mA	240-320 VDC	1.86 A	1.48 A	1.07 A	514 W	2056 W
6	LTS/LTL	1400 mA	240-320 VDC	1.86 A	1.48 A	1.07 A	514 W	3084 W



www.kenall.com | P: 800-4-Kenall | F: 262-891-9700 | 10200 55th Street Kenosha, Wisconsin 53144, USA
 This product can comply with the latest domestic preference legislation, such as the Buy American Act (BAA), Trade Agreement Act (TAA), Build America, Buy America Act (BABA), and others. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2024 Kenall Mfg. Co.

A brand of **legrand**

LUXTRAN™

Remote Driver for Tunnel Applications


RD700 SERIES

CIRCUIT DETAIL

Product Series	Lamp Power	Size Configuration	Driver Wiring Diagram	(x) Required Driver Output Current
LTS	192L	A2	A2-1	1400 mA
	295L/300L	A2	A2-2	1050 mA
	390L/400L	A2	A2-2	1400 mA
	384L/396L	B2	B2-2	1400 mA
	590L/600L	B2	B2-3	1050 mA (2)
	780L/800L	B2	B2-3	1400 mA (2)
LTL	100L	8	L1	1400 mA

Note: Specify drive current based upon intended Lamp Power for the respective product series.

WIRING SCHEMATIC



WIRE RUN DISTANCE ALLOWANCE

Wire Type	Maximum Run to Load*
18 AWG	150 ft (45 m)
16 AWG	300 ft (90 m)
14 AWG	450 ft (137 m)

*Assumes return path of equal distance



www.kenall.com | P: 800-4-Kenall | F: 262-891-9700 | 10200 55th Street Kenosha, Wisconsin 53144, USA
 This product can comply with the latest domestic preference legislation, such as the Buy American Act (BAA), Trade Agreement Act (TAA), Build America, Buy America Act (BABA), and others. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2024 Kenall Mfg. Co.

A brand of Legrand

LUXTRAN™
Remote Driver for Tunnel Applications

RD700 SERIES

DIMENSIONAL DATA

