TEKLINK™ TL1000/2000 FOR TEKDEK™

Control System Specification

TD-TL1000/2000 SYSTEM

PRODUCT FEATURES:

- » Wireless OR Wired Communication
- » Configure System through Web Browser
- » Integral Occupancy Detection
- » Report Energy Consumption
- » Monitor Occupancy Events



PROJECT INFORMATION			
Job Name			
Fixture Type			
Catalog Number			
Approved by			

SPECIFICATIONS:

PRODUCT BRIEF: TekLink™ TL1000 and TL2000 are cloud-based, adaptive lighting control systems that utilize wired and wireless (respectively) communication between system nodes. The system consists mainly of luminaire-integrated lighting controllers (BORGs), integrated Sensors, Bridges, and a Gateway. This specification provides information on the luminaire level control components. Please see the Bridge and Gateway Specification sheet for additional system information.

TEKLINK TL1000/2000 BORG: Integral controllers located in LED luminaires, sensors, and as stand-alone devices; BORGs (Board on Radio Grid) process data and record system activity. The LED luminaires react to changes in the environment based on a programmable lighting schedule. TL1000 BORGs utilize wired (shielded twisted pair) communication to exchange information built on the CAN bus protocol. TL2000 BORGs use wireless communication (900 MHz), designed to the IEEE 802.15.4 standard.

TEKLINK SENSOR: Operates by low-voltage power provided by the BORG or LED driver and provides Microwave (MW) occupancy detection with integral light level sensing.


SIDE VIEW


INSTALLATION: Control components and sensor housing pre-attached to TD17 housing at factory.

WARRANTY: Limited five (5) year warranty.





DIMENSIONAL DATA





Product dimensions with embedded TL1000/2000 controller and Microwave sensor (standard)






Product dimensions with embedded TL1000/2000 controller and Passive Infrared sensor (non-standard, available upon request)

Lens Option	Lens Angle	Maximum Coverage	Mounting Height
L488	360°	48' diameter	8'
L6020	360°	60' diameter	20'


MICROWAVE SENSOR COVERAGE PATTERN



Ceiling mounted detection pattern

NOTE: Occupancy pattern dimensions are maximums, may vary due to environment

L488 Lens



L6020 Lens

